



CATALYST SB WF 002

Catalyst SB WF 002 is a solution of Phosphoric Acid in Isopropanol manufactured with a high quality grade of acid to provide optimum properties.

ADVANTAGES

- : Fast cure.
- Excellent weathering and exterior durability.
- High Gloss.

Typical Properties

- : Appearance : Clear, light straw
- : % Active : 33%
- : Acid Value : 135
- : S.G. : 0.9 grams per cm²
- : Volatile : Isopropanol /Ethanol
- : Gardner Colour : 1

Solubility

- : Soluble in water, alcohols, glycol ethers, glycols.
- Soluble in aromatic and aliphatic hydrocarbons.

Applications

- : Wood coatings
- Appliance finishes
- General industrials

Typical Usage Levels

- : 0.25 - 1.0% as supplied on total resin solids.

Incorporation

- : May be added to the coating with agitation as supplied or pre-diluted with alcohol.

Shelf Life

- : 24 months from the date of manufacture, when stored at ambient conditions in the originals container.

Handling & Storage

- : Catalyst SB WF 002 is classified as a flammable and corrosive liquid. Safe handling of this product should include the use of safety glasses and gloves. Avoid breathing vapours, use with adequate ventilation. Product should be stored in lined treated glass containers away from sunlight and excessive heat. Avoid contact with ferrous metal or mild steel. Refer to Material Safety Data Sheet for detailed information.

Packaging

- : 0.8 litres - 1 litre or as per customers requirements.